



BOSCHERT GIZELIS USA

Gcut[®] series



- Swing beam hydraulic shear
- Color touch screen control-10.4"
- High speed CNC back gauge - 39"
- Squaring arm with linear scale - 39"
- Front support arms with linear scale
- Adjustable cutting length
- Adjustable hold down pressure
- Ball transfer table
- Operator protection via front safety fence or optional light curtain
- Operator protection via rear side guards with photo cell
- Programmable control with optional features

Optional Features:

- Sheet support system
- Automatic thickness measurement
- Return to front
- Narrow strip cutting



		G Cut CNC® 2504	G Cut CNC® 3006	G Cut CNC® 3010	G Cut CNC® 3013	G Cut CNC® 3016	G Cut CNC® 3020	G Cut CNC® 4006	G Cut CNC® 4010	G Cut CNC® 4013	G Cut CNC® 4016	G Cut CNC® 4020	G Cut CNC® 6006	G Cut CNC® 6010	G Cut CNC® 6013
Max mild steel S142	[in.]	0.16	0.24	0.39	0.51	0.63	0.79	0.24	0.39	0.51	0.63	0.79	0.24	0.39	0.51
Max stainless steel	[in.]	0.08	0.16	0.24	0.31	0.39	0.47	0.16	0.24	0.31	0.39	0.47	0.16	0.24	0.31
Cutting length	[in.]	102	122	122	122	122	122	161	161	161	161	161	240	240	240
Throat depth	[in.]	6	7	8	8	8	10	7	9	9	9	9	12	12	12
Back gauge length	[in.]	39	39	39	39	39	39	39	39	39	39	39	39	39	39
Cutting angle	[°]	1.26	1.42	1.79	1.97	2.33	2.85	1.49	1.91	2.05	2.18	2.20	1.46	1.5	1.5
Maximum hydraulic pressure	[bar]	255	255	255	255	255	255	255	255	255	255	255	255	255	255
Main motor power	[h.p.]	10	15	20	30	40	50	15	20	30	40	50	20	30	40
Length	[in.]	136	156	156	156	156	156	195	195	195	195	205	274	274	274
Width	[in.]	138	154	161	177	177	177	154	161	177	189	189	161	177	177
Height	[in.]	77	77	81	87	100	100	81	79	89	100	106	79	94.5*	94.5*
Weight	[lbs]	13000	18000	23000	28000	37000	52000	26000	33000	37000	52000	61000	48000	61000	79000

* The machine is partially in the ground. (special foundation required)



GFLEX series



GBEND plus series



GCUT series



FIBER LASER



ROBOBEND



PUNCH/LASER

Boschert Precision Machinery, Inc.

12400 W. Cameron Avenue, PO Box 409,
Butler, WI 53007, T. 262-783-7816,

sales@boschertusa.com, www.boschertusa.com