

RAE

ASYMMETRICAL 3-ROLLS BENDING MACHINE



Capacity : 1,5 – 3 mm – Length : 1-2 m

Standard Equipment

- ✓ Built in cast iron on very rigid profile frame
- ✓ Self-lubricating bearings
- ✓ Pre-bending roll movement by handwheel, complete with accurate position indicator
- ✓ Top and pinch roll driven by electromechanical geared motor with brake
- ✓ Double safety foot pedal for roll rotation
- ✓ Easy to open by removal of parts

Options

- ✓ Heat treatment of rolls (hardening HF for hardness 50/60 HRC)
- ✓ Help device for occasional cone bending



CAPACITIES

All the technical information for our RAE product can be found in our web site by scanning this flash code. Look at the photo gallery or watch the video ...



3 Rolls	Capacities		Rolls diameter (mm)	Electric Power (kw)	Dimensions (Length x width x height) (mm)	Weight (kg)
	Useful rolls length	Maximal thickness				
	(mm)	(mm)				
RAE 1025	1020	2,5	90	1,1	1800 x 600 x 1200	520
RAE 1030	1020	3	114	1,5	1800 x 600 x 1200	620
RAE 1520	1520	2	90	1,1	2300 x 600 x 1200	690
RAE 1525	1520	2,5	114	1,5	2300 x 600 x 1200	780
RAE 2015	2020	1,5	90	1,1	2800 x 600 x 1200	850
RAE 2020	2020	2	114	1,5	2800 x 600 x 1200	940

* Technical capacities are given for Steel S 235 (Yield Strength 240 N/mm²)