

4 Rolls	Bending length	Top roll Diameter (D)	* Maximum Thickness (mm)				Motor power	
			1,3 x D		5 x D			
	(mm)	(mm)	Bending	Prebending	Bending	Prebending	Kw	
R4C 205-10	1 100	205	12	10	14	11	5,5	
R4C 235-10		235	14	12	16	14	7,5	
R4C 205-15	1 600	205	10	8	12	9	5,5	
R4C 235-15		235	12	10	14	12	7,5	
R4C 205-20	2 100	205	8	6	10	8	5,5	
R4C 235-20		235	10	8	12	10	7,5	
R4C 265-20		265	12	10	14	12	11	
R4C 285-20		285	14	12	16	14	15	
R4C 350-20		350	24	20	26	22	22	
R4C 400-20		400	30	25	33	28	30	
R4C 450-20		450	35	30	37	32	37	
R4C 460-20		460	37	32	39	34	45	
R4C 205-25		2 600	205	7	5	9	7	5,5
R4C 235-25			235	9	7	11	10	7,5
R4C 265-25	265		11	9	13	11	11	
R4C 285-25	285		13	11	15	13	15	
R4C 350-25	350		22	18	24	20	22	
R4C 400-25	400		27	22	30	26	30	
R4C 450-25	450		32	27	35	30	37	
R4C 460-25	460		34	29	37	32	45	
R4C 205-30	3 100	205	6	4	8	6	5,5	
R4C 235-30		235	8	6	10	8	7,5	
R4C 265-30		265	10	8	12	10	11	
R4C 285-30		285	12	10	14	12	15	
R4C 350-30		350	20	15	22	18	22	
R4C 400-30		400	25	20	28	24	30	
R4C 450-30		450	30	25	33	28	37	
R4C 460-30		460	32	27	35	30	45	
R4C 205-40	4 100	205	3	2	4	3	5,5	
R4C 235-40		235	4	3	6	4	7,5	
RCS 265-40		265	6	4	8	6	11	
RCS 285-40		285	8	6	10	8	15	
RCS 350-40		350	14	10	15	12	22	
RCS 360-40		360	15	11	16	13	22	
R4C 400-40		400	18	14	20	16	30	
R4C 450-40		450	22	18	24	20	37	
R4C 460-40		460	24	20	26	22	45	